



Smart solutions guide for the Marine industry

PRODUCT CATALOGUE





Index

4 PRIMERS/CLEANERS

16 PICTOGRAMS

18 DECK BONDING

24 DECK CAULKING

28 ARTIFICIAL DECK BONDING

34 WINDOW BONDING & SEALING

40 GENERAL BONDING & SEALING

46 DECK TO SPIDER/HULL BONDING

56 INTERIOR BONDING

64 INFLATABLE



Primer/Cleaners

PRETREATMENT, PART OF A SMART SYSTEM SOLUTION





Simson Cleaner I

SIMSON CLEANER I IS A PREPARATION AGENT, IDEALLY SUITABLE FOR CLEANING AND DEGREASING SUBSTRATES FOR BONDING OR SEALING WITH SPECIFIC SIMSON PRODUCTS.

- Cleaning and degreasing of ceramic coated glass.
- Cleaning and degreasing of plastic.
- Cleaning and degreasing of closed substrates (consult Bostik for more information).



	Code article	Colour	Packaging
Cleaner I	30024054	Transparent	2,5 L





Simson Cleaner E

SIMSON CLEANER E IS A PREPARATION AGENT, IDEALLY SUITABLE FOR CLEANING AND DEGREASING SUBSTRATES FOR BONDING OR SEALING WITH SPECIFIC SIMSON PRODUCTS.

- **Cleaning and degreasing of teakwood decks (prior to the application of Simson Prep P).**
- **Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP), silicones, polysulphide and polyurethane from substrates and tools.**
- **Degreasing and cleaning glass substrates.**



	Code article	Colour	Packaging
Cleaner E	30023360	Transparent	500 ml





Simson Liquid 1

SIMSON LIQUID 1 IS A THIN LIQUID CLEANING AGENT FOR SURFACES AND TOOLS ESPECIALLY TO REMOVE FRESH REMAINS OF PRIMERS, SEALANTS AND ADHESIVES.

- Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP), silicones and polyurethane from substrates and tools.



	Code article	Colour	Packaging
Liquid 1	30025380	Transparent	1 L





Simson Cleaner 14

SIMSON CLEANER 14 IS A THIN LIQUID PRODUCT FOR CLEANING AND DEGREASING SUBSTRATES BEFORE SEALING OR BONDING WITH SPECIFIC SIMSON PRODUCTS.

- Cleaning and degreasing of closed substrates.
- Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP), silicones and polyurethane from substrates and tools.



	Code article	Colour	Packaging
Cleaner 14	30022100	Transparent	1 L





Simson Prep P

SIMSON PREP P IS A LIQUID PRETREATMENT FOR IMPROVING THE ADHESION OF SEVERAL SIMSON PRODUCTS ON POROUS SUBSTRATES.

- Pretreatment of wooden substrates.
- Pretreatment of teak ship decks.



	Code article	Colour	Packaging
Prep P	30023300	Transparent	500 ml





Simson Prep M

SIMSON PREP M IS A ONE-STEP PRETREATMENT FOR THE IMPROVEMENT OF THE ADHESION ON CLOSED SUBSTRATES OF SEVERAL SPECIFIC SIMSON PRODUCTS, BASED ON SILYL MODIFIED POLYMER (SMP).



- Degreasing and pretreatment of closed substrates.
- Easy to use one-step process.
- Efficient in use.

	Code article	Colour	Packaging
Prep M	30022110	Transparent	500 ml





Simson Prep K

SIMSON PREP K IS A PRETREATMENT TO IMPROVE THE ADHESION OF SEVERAL SPECIFIC SIMSON PRODUCTS, BASED ON SILYL MODIFIED POLYMER (SMP), MAINLY FOR PLASTIC SUBSTRATES.

- Pretreatment of hard and soft PVC, like artificial deck.
- Pretreatment of plastics like ABS.



	Code article	Colour	Packaging
Prep K	30022830	Transparent	500 ml





Simson Prep G

SIMSON PREP G HAS BEEN DEVELOPED AS A BLACK PRETREATMENT FOR USE ON GLASS, WITHOUT A CERAMIC COATING, IN ORDER TO PROVIDE A UV-PROTECTING COAT, BEFORE APPLYING SPECIAL ADHESIVES FOR BONDING GLASS (ALSO PMMA, ACRYLIC AND PC).

- **Black pretreatment of glass, acrylic and PC substrates without ceramic coating.**
- **Repair of damaged paint layers on metallic supports.**



	Code article	Colour	Packaging
Prep G	30023511	Black	250 ml





Simson Finishing Soap

SIMSON FINISHING SOAP IS A MIXTURE OF SPECIAL TENSIDES. THIS PRODUCT IS IDEAL FOR FINISHING AND TOOLING SEALANT JOINTS ANY DANGER OF YELLOWING / DISCOLORATION OF SEALANT JOINTS, THAT MAY OCCUR WHILE USING STANDARD SOAP SUDS, IS NOT POSSIBLE WITH SIMSON FINISHING SOAP BECAUSE OF THE ABSENCE OF COLOURING- AND PRESERVING AGENTS. (NB TENSIDES ARE WATER SOLUBLE SUBSTANCES THAT INFLUENCE THE SURFACE TENSION OF LIQUIDS).



- Ready for use.
- Colourless; does not cause discoloration or fading of sealants.
- pH neutral.

	Code article	Colour	Packaging
Simson Finishing Soap	30608173	Transparent	1000 ml







Pictograms

Pretreatment

In the previous chapter, we have explained which primers and cleaners we offer for the different applications in the marine industry. In the following chapters we will provide more information about the product ranges we offer for boat manufacturing. For each product we indicate, with the pictograms below, which primer or cleaner is used with that specific product. In case you need additional information, you can consult the Technical Data Sheets on www.bostik.com.

I SIMSON CLEANER I

E SIMSON CLEANER E

1 SIMSON LIQUID 1

14 SIMSON CLEANER 14

P SIMSON PREP P

M SIMSON PREP M

K SIMSON PREP K

G SIMSON PREP G

S SIMSON FINISHING SOAP



Deck (artificial) Bonding

A QUALITATIVE BASE FOR A DURABLE TEAK DECK





Simson STR 140

SIMSON STR 140 IS A 1-COMPONENT, MOISTURE CURING POLYURETHANE ADHESIVE. IT IS HIGHLY ELASTIC, HAS A GOOD SLUMP RESISTANCE AND CURES AT LOW HUMIDITY AND VACUUM PRESSING. STR 140 IS AS BEDDING COMPOUND BETWEEN STEEL, ALUMINUM, POLYESTER AND/ OR WOODEN (PRE-FAB) DECKS AND TEAK STROKES. ALSO SUITABLE FOR BONDING WATERTIGHT PLYWOOD SUBDECK ON A STEEL, ALUMINUM, POLYESTER OR WOODEN SUBDECK.

- Very good ageing properties.
- Long open time.
- Fast curing, excellent for vacuum pressing.



	Code article	Colour	Packaging
STR 140	30611839	Black	600 ml





Simson MSR Construction Adhesive sskf

SIMSON MSR CONSTRUCTION ADHESIVE SSKF IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). IT IS THE LONGER OPEN TIME VERSION OF THE MSR CONSTRUCTION ADHESIVE. THIS PRODUCT HAS BEEN DEVELOPED FOR BONDING AND SEALING APPLICATIONS IN THE YACHT- AND BOAT BUILDING INDUSTRY. MSR CONSTRUCTION ADHESIVE SSKF HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653(16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and aging properties; long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Neutral, odourless and fast curing.
- Long assembly time also in hot climate conditions.



	Code article	Colour	Packaging
MSR CA SSKF	30131950	White	290 ml
MSR CA SSKF	30136530	White	600 ml
MSR CA SSKF	30131970	Black	290 ml
MSR CA SSKF	30610720	Black	400 ml
MSR CA SSKF	30133090	Black	600 ml
MSR CA SSKF	30134660	Brown	290 ml
MSR CA SSKF	30131960	Grey	290 ml



2690





Simson MSR Bedding Compound

MSR BEDDING COMPOUND IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING ADHESIVE/SEALANT, BASED ON SILYL MODIFIED POLYMER (SMP). MSR BEDDING COMPOUND HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Permanently elastic in a temperature range of -40°C to +100°C.
- MSR Bedding Compound has sound- and vibration deadening properties.



	Code article	Colour	Packaging
MSR BC	30137334	Black	600 ml
MSR BC	30137333	Black	20 L
MSR BC	30133040	Light grey	290 ml
MSR BC	30133050	Light grey	600 ml
MSR BC	30607954	Teak brown	600 ml



2690





Bostik Marocol PU 2D480

MAROCOL PU2D480 IS A SOLVENT FREE THIXOTROPIC 2-COMPONENT POLYURETHANE CONSTRUCTION ADHESIVE. MAROCOL PU2D480 IS DEVELOPED FOR STRUCTURAL BONDING OF (ARTIFICIAL) TEAK TO DECK. DUE TO ITS LONG OPEN TIME, IT IS VERY SUITABLE TO BOND LARGE SURFACES IN ONE TIME

- Solvent free.
- Long open time of 120 minutes.
- Easy and fast application.
- High gap filling



	Code article	Colour	Packaging
Marocol PU 2D480	30179617	Beige	7 kg
Hardner 4300	30172413	Brown	1.17 kg









Deck Caulking

A DURABLE FINISH FOR AN AESTHETIC TEAK DECK





Simson MSR Deck Caulk Advanced

SIMSON MSR DECK CAULK ADVANCED IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING SEALANT, BASED ON SILYL MODIFIED POLYMER (SMP). MSR DECK CAULK ADVANCED HAS EXCELLENT CHEMICAL, UV AND HEAT RESISTANCE.

- Solvent- and isocyanate free.
- Very good UV-resistance and ageing properties; long time resistance against fresh and salt water.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Can be sanded after curing.
- Good chemical resistance.



E

P

	Code article	Colour	Packaging
MRS DC Advanced	30605609	Black	290 ml
MRS DC Advanced	30604732	Black	600 ml
MRS DC Advanced	30606468	Black	20 L
MRS DC Advanced	30606365	Black	200 L





Simson MSR Deck Caulk S

SIMSON MSR DECK CAULK S IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING SEALANT, BASED ON SILICONE (S). MSR DECK CAULK S HAS EXCELLENT CHEMICAL, UV AND HEAT RESISTANCE.



- **Primerless application.**
- **Very good UV-resistance and ageing properties; long time resistance against fresh and salt water.**
- **Permanently elastic in a temperature range of -40°C to +110°C.**
- **Neutral, oxim and fast curing.**
- **High chemical resistance**

E

	Code article	Colour	Packaging
MSR DC S	30613914	Grey	600 ml





Window Bonding & Sealing

QUALITY SOLUTIONS FOR WINDOW APPLICATIONS





Simson MSR Construction Adhesive

SIMSON MSR CONSTRUCTION ADHESIVE IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). MSR CONSTRUCTION ADHESIVE HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and ageing properties; long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to $+100^{\circ}\text{C}$.
- Neutral, odourless and fast curing.



2690



	Code article	Colour	Packaging
MSR CA	30131910	Black	290 ml
MSR CA	30131880	White	290 ml





Simson MSR Construction Adhesive sskf

SIMSON MSR CONSTRUCTION ADHESIVE SSKF IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). IT IS THE LONGER OPEN TIME VERSION OF THE MSR CONSTRUCTION ADHESIVE. THIS PRODUCT HAS BEEN DEVELOPED FOR BONDING AND SEALING APPLICATIONS IN THE YACHT- AND BOAT BUILDING INDUSTRY. MSR CONSTRUCTION ADHESIVE SSKF HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653(16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and aging properties; long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to $+100^{\circ}\text{C}$.
- Neutral, odourless and fast curing.
- Long assembly time also in hot climate conditions.



I	G	S	M
Code article			
		Colour	Packaging
MSR CA SSKF	30131950	White	290 ml
MSR CA SSKF	30136530	White	600 ml
MSR CA SSKF	30131970	Black	290 ml
MSR CA SSKF	30610720	Black	400 ml
MSR CA SSKF	30133090	Black	600 ml
MSR CA SSKF	30134660	Brown	290 ml
MSR CA SSKF	30131960	Grey	290 ml



Simson MSR Fast Tack

SIMSON MSR FAST TACK IS A PERMANENTLY ELASTIC, 1-COMPONENT ADHESIVE BASED ON SILYL MODIFIED POLYMER (SMP) WITH A HIGH GREEN STRENGTH, AN EXCELLENT UV STABILITY AND FRESH AND SALT WATER RESISTANCE. MSR FAST TACK IS ESPECIALLY DESIGNED FOR WINDOW BONDING. MSR FAST TACK HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Reduced or no clamping needed due to high green strength (internal strength).
- Solvent- and isocyanate free.
- Very good UV-resistance and ageing properties.
- In general good adhesion on several substrates without the use of a primer, e.g. ceramic coated glass, PMMA and PC.
- Permanently elastic in a temperature range of -40°C to +100°C.



I G S M

	Code article	Colour	Packaging
MSR FT	30136121	Black	290 ml
MSR FT	30606409	Black	600 ml
MSR FT	30132913	White	290 ml
MSR FT	On request	White	600 ml



2690







General Bonding & Sealing

VERSATILE SOLUTIONS FOR VARIOUS APPLICATIONS






Simson MSR Construction Adhesive

SIMSON MSR CONSTRUCTION ADHESIVE IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). MSR CONSTRUCTION ADHESIVE HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and ageing properties;
long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Neutral, odourless and fast curing.



2690

	Code article	Colour	Packaging
MSR CA	30131910	Black	290 ml
MSR CA	30131880	White	290 ml





Simson MSR Construction Adhesive sskf

SIMSON MSR CONSTRUCTION ADHESIVE SSKF IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). IT IS THE LONGER OPEN TIME VERSION OF THE MSR CONSTRUCTION ADHESIVE. THIS PRODUCT HAS BEEN DEVELOPED FOR BONDING AND SEALING APPLICATIONS IN THE YACHT- AND BOAT BUILDING INDUSTRY. MSR CONSTRUCTION ADHESIVE SSKF HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653(16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and aging properties; long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Neutral, odourless and fast curing.
- Long assembly time also in hot climate conditions.



	Code article	Colour	Packaging
MSR CA SSKF	30131950	White	290 ml
MSR CA SSKF	30136530	White	600 ml
MSR CA SSKF	30131970	Black	290 ml
MSR CA SSKF	30610720	Black	400 ml
MSR CA SSKF	30133090	Black	600 ml
MSR CA SSKF	30134660	Brown	290 ml
MSR CA SSKF	30131960	Grey	290 ml



2690





Simson Fireseal S

SIMSON FIRESEAL S (ILICONE) IS A FIRE-RETARDANT, NEUTRAL CURING SILICONE SEALANT, SUITABLE FOR BOTH INSIDE AND OUTSIDE APPLICATIONS IN SHIP/YACHT BUILDING. FOR SEALING (CONNECTION) JOINTS, AROUND WINDOW FRAMES, OUTLETS THROUGH WALLS AND FLOORS OF PIPES, CABLES, VENTILATION DUCTS, ETC.

- Solventfree and free of halogenated additives.
- Permanently elastic.
- Good UV- and weather resistance.
- Tested on fire resistance by a.o. TNO and Warrington.
- Complies to DIN 4102 class B1.
- Tested according to IMO-resolution A.687 (17).



	Code article	Colour	Packaging
Fireseal S	30131410	White	290 ml







Deck to Spider/Hull bonding

A SOLID SOLUTION FOR STRUCTURAL BONDING





XPU 18018

BOSTIK XPU 18018 IS A FAST, 2-COMPONENT, POLYURETHANE BASED ADHESIVE CURING AT ROOM TEMPERATURE AS WELL AS AT HIGHER TEMPERATURES. XPU 18018 IS SPECIFICALLY DEVELOPED FOR STRUCTURAL BONDING. DUE TO ITS VERY SHORT CLAMPING TIME, IT IS VERY SUITABLE FOR FAST PRODUCTION.

- Solventfree, does not contain mercury salt.
- Very short clamping time.
- High strength.



	Code article	Colour	Packaging
XPU 18018	30170560	Grey	400 ml
XPU 18018 (A)	30160610	Grey	30 kg
XPU 18018 (B)	30160620	Grey	21 kg





XPU 18560M

BOSTIK XPU 18560M IS A SOLVENTFREE, 2-COMPONENT, POLYURETHANE ADHESIVE THAT CURES IN A WIDE RANGE OF TEMPERATURES. XPU 18560M IS SPECIFICALLY DEVELOPED FOR STRUCTURAL BONDING, DUE TO ITS MEDIUM CLAMPING TIME IT IS VERY SUITABLE FOR SPIDER TO HULL BONDING.

- Solventfree, does not contain mercury salt.
- Easy and fast application.
- High gap filling.
- Controlled curing.
- Medium open time.



	Code article	Colour	Packaging
XPU 18560M	30603670	Grey	400 ml
XPU 18560M (A)	30603135	Grey	30 kg
XPU 18560M (B)	30603136	Beige	25.8 kg





XPU 18570

BOSTIK XPU 18570 IS A SOLVENTFREE, 2-COMPONENT, POLYURETHANE ADHESIVE THAT CURES IN A WIDE RANGE OF TEMPERATURES. XPU 18570 IS SPECIFICALLY DEVELOPED FOR STRUCTURAL BONDING, DUE TO ITS LONG OPEN TIME IT IS VERY SUITABLE FOR (LARGE) DECK TO HULL BONDING.

- Solventfree, does not contain mercury salt.
- Easy and fast application.
- High gap filling.
- Good water resistance.
- Long open time.



	Code article	Colour	Packaging
XPU 18570 (A)	30604350	Light blue	30 kg
XPU 18570 (B)	30604464	Light blue	25.8 kg





Butyl tape 1188

THERMOPLASTIC BUTYL TAPE 1188 IS SUITABLE FOR SEALING OF PLASTIC FOIL. THIS PRODUCT IS SPECIFICALLY DEVELOPED FOR THE VACUUM PROCESS OF POLYESTER PARTS.

- Permanent plastic and permanent tacky.
- 100% airtight.
- Good water vapour tightness.
- Adhesion to almost all substrates.



	Code article	Colour	Packaging
Butyl tape 1188	30602337	Black	15 m





Bostik SAF30 15

BOSTIK SAF STRUCTURAL ARE REVOLUTIONARY AND PERFECT FOR ALL MARINE APPLICATION. PROTECTING ALL COMPOSITES RESINS WITH LOW EXOTHERM REACTION AND VERY LOW SHRINKAGE, SAF STRUCTURAL ADHESIVE AVOIDS READ THROUGH AND STRESSES ON TO THE COMPOSITES. SAF HIGH THIXOTROPIC PROPERTIES ALLOWS LARGE BEAD APPLICATION ON VERTICAL SURFACE AND REDUCE BY FAR DISPENSING TIME. SAF ALLOWS YOU TO USE FASTER CURING PRODUCTS THAN USUAL AND REDUCE YOUR PRODUCTION COSTS. BOSTIK SAF30 RANGE IS BUREAU VERITAS CERTIFIED FOR ALL STRUCTURAL APPLICATION IN MARINE INDUSTRY.

- **Fast curing**
- **Minimal surface preparation**
- **Excellent durability**
- **Bureau Veritas certified**



	Code article	Colour	Packaging
Bostik SAF30 15	On request	Off-White	50 ml
Bostik SAF30 15	On request	Black	50 ml
Bostik SAF30 15	On request	Off-White	490 ml
Bostik SAF30 15	On request	Black	490 ml
Bostik SAF30 15	On request	Black or White	20 L
Bostik SAF30 15	On request	Black or White	20 L
Bostik SAF30 15	On request	Black or White	200 L
Bostik SAF30 15	On request	Black or White	200 L



BUREAU
VERITAS





Bostik SAF30 45

BOSTIK SAF STRUCTURAL ARE REVOLUTIONARY AND PERFECT FOR ALL MARINE APPLICATION. PROTECTING ALL COMPOSITES RESINS WITH LOW EXOTHERM REACTION AND VERY LOW SHRINKAGE, SAF STRUCTURAL ADHESIVE AVOIDS READ THROUGH AND STRESSES ON TO THE COMPOSITES. SAF HIGH THIXOTROPIC PROPERTIES ALLOWS LARGE BEAD APPLICATION ON VERTICAL SURFACE AND REDUCE BY FAR DISPENSING TIME. SAF ALLOWS YOU TO USE FASTER CURING PRODUCTS THAN USUAL AND REDUCE YOUR PRODUCTION COSTS. BOSTIK SAF30 RANGE IS BUREAU VERITAS CERTIFIED FOR ALL STRUCTURAL APPLICATION IN MARINE INDUSTRY.

- Medium curing time
- High modulus
- Bureau Veritas certified



	Code article	Colour	Packaging
Bostik SAF30 45	On request	Off-White	490 ml
Bostik SAF30 45	On request	Black	490 ml
Bostik SAF30 45	On request	Black or White	20 L
Bostik SAF30 45	On request	Black or White	20 L
Bostik SAF30 45	On request	Black or White	200 L
Bostik SAF30 45	On request	Black or White	200 L



BUREAU
VERITAS





Bostik SAF30 LOT

BOSTIK SAF STRUCTURAL ARE REVOLUTIONARY AND PERFECT FOR ALL MARINE APPLICATION. PROTECTING ALL COMPOSITES RESINS WITH LOW EXOTHERM REACTION AND VERY LOW SHRINKAGE, SAF STRUCTURAL ADHESIVE AVOIDS READ THROUGH AND STRESSES ON TO THE COMPOSITES. SAF HIGH THIXOTROPIC PROPERTIES ALLOWS LARGE BEAD APPLICATION ON VERTICAL SURFACE AND REDUCE BY FAR DISPENSING TIME. SAF ALLOWS YOU TO USE FASTER CURING PRODUCTS THAN USUAL AND REDUCE YOUR PRODUCTION COSTS. BOSTIK SAF30 RANGE IS BUREAU VERITAS CERTIFIED FOR ALL STRUCTURAL APPLICATION IN MARINE INDUSTRY.

- Long open time
- Non sagging, high gap fill even on vertical surface
- Bureau Veritas Certified



	Code article	Colour	Packaging
Bostik SAF30 LOT	On request	White	490 ml
Bostik SAF30 LOT	On request	White	825 ml
Bostik SAF30 LOT	On request	White	20 L
Bostik SAF30 LOT	On request	White	200 L





Bostik SAF150 15

BOSTIK SAF STRUCTURAL ARE REVOLUTIONARY AND PERFECT FOR ALL MARINE APPLICATION. PROTECTING ALL COMPOSITES RESINS WITH LOW EXOTHERM REACTION AND VERY LOW SHRINKAGE, SAF STRUCTURAL ADHESIVE AVOIDS READ THROUGH AND STRESSES ON TO THE COMPOSITES. SAF HIGH THIXOTROPIC PROPERTIES ALLOWS LARGE BEAD APPLICATION ON VERTICAL SURFACE AND REDUCE BY FAR DISPENSING TIME. SAF ALLOWS YOU TO USE FASTER CURING PRODUCTS THAN USUAL AND REDUCE YOUR PRODUCTION COSTS.

- **Fast curing**
- **Very high elongation and impact resistance**
- **Large area bonding**



	Code article	Colour	Packaging
Bostik SAF150 15	On request	Off-White	50 ml
Bostik SAF150 15	On request	Black	50 ml
Bostik SAF150 15	On request	Off-White	490 ml
Bostik SAF150 15	On request	Black	490 ml
Bostik SAF150 15	On request	Black or White	20 L
Bostik SAF150 15	On request	Black or White	20 L
Bostik SAF150 15	On request	Black or White	200 L
Bostik SAF150 15	On request	Black or White	200 L





Interior bonding

AESTHETIC SOLUTIONS FOR YACHT INTERIORS





Cofix (S)

BOSTIK COFIX (S) IS A SOLVENT- AND POLYCHLOROPRENE (PCP) BASED CONTACT ADHESIVE, SPECIFICALLY DEVELOPED FOR MARINE INTERIOR DECORATING APPLICATIONS. COFIX (S) IS TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND IS APPROVED FOR APPLICATION THROUGHOUT THE WHOLE ACCOMMODATION (BULKHEAD, CEILING AND DECK FINISH).



- **Excellent initial bond strength.**
- **Excellent temperature resistance.**
- **Fire retardant, certified to IMO A.653 (16).**
- **Flexible bondline.**



2690

	Code article	Colour	Packaging
Cofix	30602567	Yellow	5 L
Cofix S	30029820	Red	25 L





Saderflex 805 D

SADERFLEX 805 D IS A READY-TO USE DISPERSION CONTACT ADHESIVE BASED ON ACRYLIC. SADERFLEX 805 D IS TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653(16) AND IS APPROVED FOR APPLICATION THROUGHOUT THE WHOLE ACCOMMODATION (BULKHEAD, CEILING AND DECK FINISH).



- Ready to use.
- Solventfree contact adhesive.
- Long open time.
- Suitable for PVC flooring.
- Fire retardant, certified to Imo A.653(16).

	Code article	Colour	Packaging
Saderflex 805 D	30600284	White	6 kg
Saderflex 805 D	30600283	White	20 kg



2690





Simson Fireseal S

SIMSON FIRESEAL S (ILICONE) IS A FIRE-RETARDANT, NEUTRAL CURING SILICONE SEALANT. (SUITABLE FOR BOTH INSIDE AND OUTSIDE APPLICATIONS IN SHIP/YACHT BUILDING). FOR SEALING (CONNECTION) JOINTS, AROUND WINDOW FRAMES, OUTLETS THROUGH WALLS AND FLOORS OF PIPES, CABLES, VENTILATION DUCTS, ETC.

- Solventfree and free of halogenated additives.
- Permanently elastic.
- Good UV- and weather resistance.
- Tested on fire resistance by a.o. TNO and Warrington.
- Complies to DIN 4102 class B1.
- Tested according to IMO-resolution A.687 (17).



	Code article	Colour	Packaging
Fireseal S	30131410	White	290 ml






Simson MSR Construction Adhesive

SIMSON MSR CONSTRUCTION ADHESIVE IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). MSR CONSTRUCTION ADHESIVE HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653 (16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and ageing properties;
long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Neutral, odourless and fast curing.



2690

	Code article	Colour	Packaging
MSR CA	30131910	Black	290 ml
MSR CA	30131880	White	290 ml






Simson MSR Construction Adhesive sskf

SIMSON MSR CONSTRUCTION ADHESIVE SSKF IS A 1-COMPONENT, PERMANENTLY ELASTIC, FAST CURING CONSTRUCTION ADHESIVE, BASED ON SILYL MODIFIED POLYMER (SMP). IT IS THE LONGER OPEN TIME VERSION OF THE MSR CONSTRUCTION ADHESIVE. THIS PRODUCT HAS BEEN DEVELOPED FOR BONDING AND SEALING APPLICATIONS IN THE YACHT- AND BOAT BUILDING INDUSTRY. MSR CONSTRUCTION ADHESIVE SSKF HAS BEEN TESTED AND CERTIFIED TO THE INTERNATIONAL MARITIME ORGANISATION FIRE TEST PROCEDURES FOR SURFACE FLAMMABILITY, RESOLUTION A.653(16) AND HAS BEEN APPROVED FOR USE IN WALL, CEILING AND FLOOR APPLICATIONS.

- Solvent- and isocyanate free.
- Very good UV-resistance and aging properties; long time resistance against fresh and salt water.
- Good adhesion on commonly used materials without the use of a primer.
- Permanently elastic in a temperature range of -40°C to +100°C.
- Neutral, odourless and fast curing.
- Long assembly time also in hot climate conditions.



	Code article	Colour	Packaging
MSR CA SSKF	30131950	White	290 ml
MSR CA SSKF	30136530	White	600 ml
MSR CA SSKF	30131970	Black	290 ml
MSR CA SSKF	30610720	Black	400 ml
MSR CA SSKF	30133090	Black	600 ml
MSR CA SSKF	30134660	Brown	290 ml
MSR CA SSKF	30131960	Grey	290 ml



2690







Inflatable

WATERTIGHT SOLUTIONS FOR RUBBER BONDING





Bostik 2402 + hardener

BOSTIK 2402 + HARDENER BOAT ADHESIVE IS A SOLVENT-BORNE FORMULATION BASED ON POLYCHLOROPRENE RUBBER. IT OFFERS STRONG RESILIENT BONDS WHICH EXHIBIT GOOD RESISTANCE TO WATER, HUMIDITY, ETC.

- Good resistance to water, heat and UV-exposure.
- Good storage stability.
- Good adhesion to several rubbers (not plasticized PVC).
- Small packaging (250 ml).



	Code article	Colour	Packaging
Bostik 2402 + hardener	30812389	Transparent	250 ml + 10 ml







Vyncol 1520 M2 + Hardener

BOSTIK VINYCOL 1520 M2 + HARDENER IS AN ADHESIVE THAT IS SPECIFICALLY DESIGNED FOR BONDING OF SYNTHETIC MATERIALS. DUE TO ITS RESISTANCE AGAINST PLASTICIZER, VINYCOL 1520 M2 + HARDENER IS SUITABLE FOR BONDING FLEXIBLE PVC.

- Suitable for bonding coated (soft) PVC or polyurethane materials (inflatable boats, strip conveyor, etc.).
- Suitable for bonding Neoprene/Hypalon materials and possible repairs.

	Code article	Colour	Packaging
Vyncol 1520 M2	30600548	Translucent	10 L
Hardener	30506010	Transparent	800 ml





BOSTIK NE486 + Hardener

BOSTIK NE486 + HARDENER IS A SOLVENT-BORNE FORMULATION BASED ON POLYCHLOROPRENE RUBBER. IT IS USED IN CONJUNCTION WITH A HARDENER AS A TWO PART, COLD CURING ADHESIVE SYSTEM.

- Good resistance to water, heat and UV-exposure.
- Good storage stability.
- Good adhesion to several rubbers (not plasticized PVC).



	Code article	Colour	Packaging
Bostik NE486 + hardener	30602765	Translucent	1 L
Bostik NE486 + hardener	30811360	Translucent	5 L





IMX70 - CUSTOM DESIGNED AND 70FT BUILT PERFORMANCE CRUISER



Download Bostik's Marine app!



THE APP INCLUDES:

- Instruction videos
- Supporting documentation
- Calculation tool
- Dealer locator



IOS



Android

Scan the code or go to the app store and search for 'Bostik Marine Solutions'

SMART SOLUTIONS FOR THE MARINE INDUSTRY

Ship and yacht builders all over the world choose the durable performance of the MSR range and the technical support offered by Bostik's nautical specialists. For more information visit www.bostik.com

- EN :** Consult the technical information leaflet for more specific details. Safety data sheet available on request. Store in a cool and dry place.
Bostik Ltd.(UK) Tel. +44(0)1785272727 - www.bostik.co.uk
Bostik Australia Pty Ltd. Tel. +61(0)392799333 - www.bostik.com.au
- NL :** NL : Voor gedetailleerde instructies raadpleeg het technisch informatieblad. Veiligheidsinformatieblad op verzoek verkrijgbaar. Koelen droog ops laan.
Bostik B.V. (NL) Tel. +31(0)736244244 - www.bostik.nl
Bostik Belux SA-NV Tel. +32(0)92551717 - www.bostik.be
- DE :** Nähere Einzelheiten entnehmen Sie bitte unserem technischen Merkblatt. Sicherheitsdatenblatt auf Anfrage erhältlich. Lagerung an einem kühlen und trockenen Ort.
Bostik GmbH (D) Tel. +49(0)5425/801-0 - www.bostik.de
- FR :** Pour de plus amples informations, se référer à la Fiche Technique. Fiche de données de sécurité disponible sur demande. A conserver dans un endroit frais et sec.
Bostik S.A. (F) Tel. +33(0)1 49 00 90 00 - www.bostik.fr
Bostik Belux SA-NV Tel. +32(0)92551700 - www.bostik.be
- IT:** Per istruzioni dettagliate, fate riferimento alla scheda tecnica. Scheda dati di sicurezza disponibile su richiesta. Stoccare in luogo fresco e asciutto
Arkema S.r.L. (I) Tel : +39 02 93513599 - www.mydrin.it
- ES :** Para informaciones detalladas referente a la hoja de informacion. Puede solicitarse la ficha de datos de seguridad. Almacenar en un lugar fresco y seco.
Bostik S.A. (E) Tel. +34(0)935860200 - www.bostik.com.es/spain/
- PL :** Szczegółowe instrukcje znajdują się w karcie danych technicznych. Karta charakterystyki dostępna na żądanie. Przechowywać w chłodnym i suchym miejscu.
Bostik Sp. z o.o. Tel: +48 618961740 - www.bostikpolska.pl
- GR :** Συμβουλευτείτε το τεχνικό φυλλάδιο για λεπτομερείς οδηγίες. Δελτίο δεδομένων ασφαλείας παρέχεται εφόσον ζητηθεί. Φυλάσσεται σε δροσερό και ξηρό χώρο.
Bostik B.V. (NL) Tel. +31(0)736244244 - www.bostik.com/el/greece/
- SE:** Läs igenom den tekniska informationbroschyren för mer detaljerade upplysningar. Säkerhetsdatablad finns att rekvidrera. Förvaras svalt och tørt.
Bostik AB, Helsingborg, +46(0)42-195000 - www.bostik.se
- DK :** Læs den tekniske informationsbrochure igennem for mere detaljerede oplysninger. Sikkerhedsdatablad kan på anmodning rekvireres. Opbevares tørt og køligt.
Bostik A/S, +45 44841500 - www.bostik.dk
- NO :** For ytterligere informasjon, se produktatablad. Sikkerhetsdatablad er tilgjengelig på anmodning. Oppbevares tørt og kjølig.
Bostik AS, +47 69-190600 - www.bostik.no
- FI :** Lisätietoja tuotteen omasta teknisestä esitteestä. Käyttöturvallisuustiedote toimitetaan pyynnöstä. Varastoitava viileässä ja kuivassa paikassa.
Bostik Oy, Tampere, +358(0)10-8438800 - www.bostik.fi
- RU:** Для получения подробной информации проконсультируйтесь с технической спецификацией. Паспорт безопасности предоставляется по запросу. Хранить в сухом и прохладном месте.
Bostik Russia Tel. +7 495 727 31 71 - www.bostik.ru
- TR :** Daha fazla bilgi için Teknik Bilgi Formuna başvurunuz. Talep halinde güvenli bilgi formu sağlanabilir. Serin ve kuru yerde saklayınız.
Çekomastik Kimya Sanayi ve Ticaret A.Ş Tel. +90 212 8580126 - www.bostik.com.tr



**Please contact your local
Bostik representative for
more information or to
arrange trials.**

Your local representative:

Bostik SA

420, rue d'Estienne d'Orves -
92705 Colombes Cedex -

France

An Arkema company

www.bostik.com

ARKEMA
INNOVATIVE CHEMISTRY